

## SAFETY DATA SHEET

**FINITEC LATEX WOOD FILLER (WATERBASED)****Product Codes:** 71600 to 71615**Product Codes:** EC-71600 to EC-71615**SECTION 1: IDENTIFICATION****Supplier Identifier****Finitec (a division of SAMAN)**

660, rue du Filtre

Victoriaville (Quebec) G6T 0T6

Canada

Phone: 1-800-692-3662 / 819-751-2350

**Product Identifier****FINITEC LATEX WOOD FILLER (WATERBASED)****Emergency Telephone Number****CANUTEC (24 Hours): 613-996-6666****SECTION 2: HAZARD IDENTIFICATION****Hazard classification**

- Carcinogenicity – Category 1
- Reproductive Toxicity – Category 2
- Specific Target Organ Toxicity (Repeated Exposure) – Category 1 (lungs)

**Signal word****DANGER****Hazard Statements****H350** May cause cancer by inhalation.**H361** Suspected of damaging fertility or the unborn child.**H372** Causes damage to organs (lungs) through prolonged or repeated exposure.**Precautionary statements****P201** Obtain special instructions before use.**P202** Do not handle until all safety precautions have been read and understood.**P280** Wear protective gloves/protective clothing/eye protection/face protection.**P260** Do not breathe dust/fume/mist/vapours.**P264** Wash thoroughly after handling.

**P270** Do not eat, drink or smoke when using this product.

**P308 + P313** IF exposed or concerned: Get medical advice/attention.

**P405** Store locked up.

**P501** Dispose of contents/container to an approved waste disposal plant.

#### **Other hazards**

Dust may be irritating to the nose and eyes.

#### **Comments**

After the product has dried and hardened, further handling or processing may generate dust.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Hazardous Ingredients</b>	<b>CAS #</b>	<b>WT. %</b>
Crystalline silica, quartz	14808-60-7	1 - 5 %
Talc	14807-96-6	1 - 4 %
Ethylene glycol	107-21-1	0.1 – 0.7 %
Non-hazardous and other ingredients below reportable level not available > 90 %		

### **SECTION 4: FIRST-AID MEASURES**

#### **Routes of exposure**

##### **Inhalation**

If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other symptoms develop. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical aid as soon as possible.

##### **Ingestion**

Rinse mouth and then drink plenty of water.

Do not induce vomiting.

Seek medical attention if necessary.

##### **Skin Contact**

Remove contaminated clothing.

Wash thoroughly with soap and water.

If irritation develops, get medical aid.

##### **Eye Contact**

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes.

Remove contact lenses, if present and easy to do.

Get medical attention if irritation develops and persists.

Use fingers to ensure that eyelids are separated and that the eye is being irrigated.

#### **Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

#### **Medical attention and special treatment**

IF exposed or concerned: Get medical advice/attention. Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved. Show this safety data sheet to the doctor in attendance.

---

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing media**

Product will not burn or support fire.

Use any media suitable for extinguishing supporting fire.

### **Hazardous combustion products**

Nonflammable and noncombustible solid.

When heated to decomposition, may emit toxic fumes.

### **Special protective equipment and precautions**

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Move containers from fire area if this can be done without risk.

### **Further information**

Closed containers may explode when exposed to extreme heat.

During fire, gases hazardous to health may be formed.

---

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Restrict access to area until completion of clean up. Evacuate personnel to safe areas. Ensure clean up is conducted by trained personnel only.

### **Environmental precautions**

Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.

### **Methods and materials for containment and cleaning up**

Stop leak. Dike and contain spill. Pick up wipe and place into an appropriate container for cleaning up disposal. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

---

## **SECTION 7: HANDLING AND STORAGE**

### **Handling precautions**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use only with adequate ventilation.

Wear appropriate personal protective equipment.

When using, do not eat, drink or smoke.

### **Storage needs**

Keep containers from excessive heat and freezing.

Protect container from physical damage.

### **Materials to avoid**

Keep away from strong acids.

Keep away from strong bases.

Keep away from oxidizing agents.

---

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**
**Occupational Exposure Limits**

<b>Ingredient</b>	<b>ACGIH TLV TWA</b>	<b>ACGIH STEL</b>	<b>OSHA PEL</b>	<b>OSHA STEL</b>	<b>NIOSH REL</b>
Crystalline silica, quartz	0.025 mg/m <sup>3</sup> (respirable fraction)	Not available	Not available	Not available	0.05 mg/m <sup>3</sup> (respirable dust)
Talc	2 mg/m <sup>3</sup>	Not available	2 mg/m <sup>3</sup>	Not available	2 mg/m <sup>3</sup>
Ethylene glycol	50 ppm	Not available	50 ppm	Not available	Not available
Non-hazardous and other ingredients below reportable level	Not available	Not available	Not available	Not available	Not available

**Engineering controls**

Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values.

**Individual protection measures****Eye/type**

Safety glasses with side-shields.

**Clothing/type**

Wear clean long legged, long sleeved work clothes.

**Gloves/type**

Permeation resistant gloves.

**Respiratory/type**

If using in a poorly ventilated area, wear a properly fitted respirator (NIOSH approved) during exposure.

**Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice. Remove soiled clothing and wash it thoroughly before reuse.

Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities.

---

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Property</b>	<b>Value</b>
Appearance	Paste
Color	Grey
Odor	Odorless
Odor threshold	Not available
pH	7 - 8,5
Melting point (°C)	825 °C, decomposition
Freezing point (°C)	Not applicable
Initial boiling point (°C)	Not available

<b>Property</b>	<b>Value</b>
Flash point (°C), Method	Not applicable
Evaporation rate	Not available
Upper flammability limit (% vol.)	Not available
Lower flammability limit (% vol.)	Not available
Vapour pressure (mm Hg)	Not available
Vapour density (air = 1)	Not available
Relative density/Specific Gravity	0.8 – 1.7
Water solubility	Slight
Solubility in other solvents	Not available
Partition coefficient — n-octanol/water	Not available
Auto-ignition temperature (°C)	Not available
Thermal decomposition temperature	Not available
Viscosity	Not available
% volatile by volume	Not available

---

## **SECTION 10: STABILITY AND REACTIVITY**

### **Reactivity**

No hazardous reactions if stored and handled as prescribed/indicated.

### **Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

### **Possibility of hazardous reactions**

No hazardous reactions when stored and handled according to instructions. The product is chemically stable.

### **Conditions to avoid**

Keep away from incompatibles such as oxidizing agents.

### **Incompatible materials**

- Acids
- Strong oxidizing agents

### **Hazardous decomposition products**

Decomposition will not occur if handled and stored properly. In case of fire, oxides of carbon (CO and CO<sub>2</sub>), fumes and smoke may be produced.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**
**Toxicological Data for Ingredients**

<b>Ingredient</b>	<b>LC50</b>	<b>LD50</b>
Crystalline silica, quartz	Not available	500 mg/kg (oral - rat)
Talc	Not available	Not available
Ethylene glycol	10.9 mg/L (inhalation - rat, 4 h, mist)	1,600 mg/kg (oral - human); 9,530 mg/kg (dermal - rat)
Non-hazardous and other ingredients below reportable level	Not available	Not available

**Routes of exposure****Inhalation**

Inhalation of vapours may cause irritation to the nose, throat and respiratory tract.  
Dust particles may cause irritation of the respiratory tract.

**Ingestion**

Ingestion of this product may cause nausea, vomiting and diarrhea.

**Skin contact**

Contact may cause skin irritation.

**Eye contact**

Contact may cause eyes irritation.  
May cause mechanical irritation (abrasion).

**Acute effects****Acute oral toxicity**

Acute toxicity estimate > **2,000 mg/kg**.  
Virtually nontoxic after a single ingestion.  
Method: calculation method.

**Acute dermal toxicity**

**LD50 (Rabbit): > 2,000 mg/kg**  
Virtually nontoxic after a single skin contact.  
Method: calculation method.

**Acute inhalation toxicity**

Acute toxicity estimate: > **5 mg/L**.  
Test atmosphere: dust/mist.  
Exposure time: 4 h.  
Virtually nontoxic by inhalation.  
Method: calculation method.

**Skin corrosion/irritation**

Result: slight irritation.

**Serious eye damage/eye irritation**

Result: mild eye irritation.

**Respiratory or skin sensitisation**

Non-sensitizing.

**Specific target organ toxicity (STOT) single exposure**

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

**Aspiration hazard**

No aspiration hazard expected.

**Chronic toxicity/effects****Specific target organ toxicity (STOT) repeated exposure****Quartz and Cristobalite:**

May cause damage to organs (lungs) through prolonged or repeated exposure (inhalation).

**Talc:**

Repeated or prolonged inhalation of Talc dust may cause chronic cough, shortness of breath, scarring of the lungs (pulmonary fibrosis) and mild symptomatic pneumoconiosis.

**Carcinogenicity**

In June, 1997, IARC classified crystalline silica (quartz and cristobalite) as a human carcinogen. IARC states that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1). Risk of cancer depends on duration and level of exposure.

**Reproductive toxicity**

May cause adverse reproductive effects. Possible risk of harm to the unborn child (Ethylene glycol).

**Germ Cell Mutagenicity**

No known significant effects or critical hazards.

**Remarks**

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding. During spraying or sanding the product, wear suitable respiratory equipment to protect against inhalation of mist and dust. The product has not been tested. The statement has been derived from the properties of the individual components.

**Symptoms of Exposure**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further important symptoms and effects are so far not known.

---

**SECTION 12: ECOLOGICAL INFORMATION****Ecotoxicity**

May cause long-term adverse effects in the aquatic environment.

**Persistence and degradability**

No data available.

**Bioaccumulative potential**

No data available.

**Mobility in soil**

No data available.

**Other adverse effects**

No data available.

---

## **SECTION 13: DISPOSAL CONSIDERATIONS**

### **Disposal methods**

#### **Waste disposal of substance**

Dispose of in accordance with national, state and local regulations.

#### **Container disposal**

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

---

## **SECTION 14: TRANSPORT INFORMATION**

### **TDG classification**

Not regulated as a dangerous good.

---

## **SECTION 15: REGULATORY INFORMATION**

### **WHMIS regulatory status**

This product has been classified in accordance with the hazard criteria of the **Canadian Hazardous Products Regulations and the Safety Data Sheet** contains all the information required by the **Hazardous Products Regulations (WHMIS 2015)**. This product is **WHMIS 2015** controlled.

---

## **SECTION 16: OTHER INFORMATION**

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

**Source of Technical Data and WHMIS Classification**

**Original Manufacturer:**

TORCAN COATINGS INC.

**Prepared for**

**Finitec (a division of SAMAN)**

660, rue du Filtre

Victoriaville (Quebec) G6T 0T6

Canada

Phone: 1-800-692-3662 / 819-751-2350

**Original SDS Prepared By**

CanChem Consultant

**Original Manufacturer SDS Date**

October 31, 2017

**Finitec English SDS Revision Date**

June 22, 2026