

## **Finitec DESIGN Waterborne Paint Application Guide**

**Finitec DESIGN** waterborne paint is specially designed to restore interior wood that has already been finished and add color to your decor.

### **Use:**

For interior wood only, such as floors, furniture, doors, moldings, and stairs or any other wood elements.

### **Compatibility:**

Finitec DESIGN waterborne paint has been formulated to adhere to all types of coatings, whether waterborne or oil-based, or on a pre-finished floor and is compatible with all Finitec's finishes. IT IS RECOMMENDED TO TEST THE AREA FOR COMPATIBILITY AND COLOR.

### **Preparation:**

1. Thoroughly clean the surface with Finitec's Surface Preparation in order to eliminate accumulated dirt, grease, oil or waxes.
2. Abrade the surface with 120 grit sandpaper. Finitec's floor sanding machine is recommended for larger surfaces.
3. Vacuum the surface and tack to remove dust.

### **Directions for use:**

Before proceeding, if you are applying pastel colors, we recommend applying an all surface primer to maximize the opacity.

1. **Stir** the paint for 1-2 minutes with a clean stir stick to ensure homogeneity of product. Do not dilute.
2. **Apply** at room temperature between 70 °F and 77 °F (21 °C to 25 °C) and at a relative humidity between 35 and 50%. NOTE: The paint can be applied directly on bare wood.
3. **Apply** paint evenly using a 10 mm (3/8") lint free roller or brush.
4. **In most cases, 2 coats of paint are sufficient**, but additional coats may be applied to enhance appearance.
5. **Allow 2 to 3 hours** between coats for paint to dry (may vary depending on environmental conditions).
6. **After the final coat of paint is applied**, allow it to dry for 24 hours. During this period, it is recommended to keep the area ventilated. NOTE: Finitec's DESIGN paint is resistant to wear, but must be coated with finish. It is important to respect the paint's drying time before coating with a finish to ensure good adhesion.
7. **Abrade** the painted surface using a fine abrasive pad.
8. **Vacuum** the surface and tack to remove dust.
9. **Apply** 1 to 2 coats of Finitec finish. NOTE: It is recommended to apply 2 coats of finish for optimal results .
10. **Clean** tools with water after use.

**Shelf life:** At least 12 months when stored in its original container. Store in a dry and well-ventilated area. Close the container after use. **KEEP FROM FREEZING.**

**Coverage:** **Covers up to 100 sq.ft./L** (9.3 m<sup>2</sup>/L) (may vary depending on method and application conditions).

**Responsibility:** It is the responsibility of the user to read the directions of use before using the product. Visit our website at [finitec-inc.com](http://finitec-inc.com) or call our Customer Service Department at 1-888-838-4449 for more information.

**First Aid:** In case of eye or skin contact, rinse well with water for 15 minutes. In case of inhalation, allow the victim to rest in a well-ventilated area. If swallowed, seek medical attention. Do not induce vomiting. Have conscious person drink several glasses of water. **KEEP OUT OF REACH OF CHILDREN.**